

ILULA®



ILULA CHAIN BLOCK

Robust & dependable chain block that is economical & lightweight

- Range from 500kg - 20,000kg
- Double pawl braking system
- Extra-thick asbestos-free friction plates
- **Anti-slip hooks providing extra safety with heavy duty cast safety latches**
- Full spares back-up for maintenance purposes
- Drop forged top & bottom hooks that can rotate 360°
- Designed to international standards. Generally compliant to SANS
- Units can be chained for any height of lift required
- Overload protection available on request
- Each unit is tested to 125% of the rated capacity
- **Serial numbered for traceability**
- **Supplied with individual test certificate**



| Product Code | Capacity (ton) | Effort (kg) | Load Chain | | Mass @ std 3m lift (kg) | Mass for extra metre HOL (kg) |
|--------------|----------------|-------------|---------------|--------------|-------------------------|-------------------------------|
| | | | Diameter (mm) | No. of falls | | |
| ICU005 | 0.5 | 20 | 6.0 | 1 | 8.0 | 1.7 |
| ICU010 | 1.0 | 33 | 6.0 | 1 | 12.0 | 1.7 |
| ICU015 | 1.5 | 37 | 8.0 | 1 | 18.0 | 2.3 |
| ICU020 | 2.0 | 37 | 8.0 | 1 | 18.0 | 2.3 |
| ICU030 | 3.0 | 39 | 8.0 | 2 | 25.0 | 3.7 |
| ICU030S | 3.0 | 42 | 10.0 | 1 | 28.0 | 3.1 |
| ICU050 | 5.0 | 44 | 10.0 | 2 | 45.0 | 5.4 |
| ICU100 | 10.0 | 44 | 10.0 | 4 | 79.0 | 9.7 |
| ICU200 | 20.0 | 44 x 2 | 10.0 | 8 | 193.0 | 19.4 |

OVERLOAD PROTECTION

Available on request